

TAYLOR STUDIOS

PO Box 847, Kingshill, VI. 00851 340-718-1364

www.taylorstudiosvi.com

STONE SEALER CONCENTRATE

TECHNICAL DATA SHEET

STONE SEALER CONCENTRATE is a concentrated reactive silicone polymer in mineral spirits that chemically bonds to form an invisible barrier on all types of interior and exterior stone or concrete surfaces including marble, granite, slate, limestone, sandstone, terrazzo and concrete brick and tile.

The coverage rate will vary depending on the porosity of the surface but it is normally in the range of 500 to 1,000 sq ft per gallon per application and three applications are recommended for concrete surfaces.

APPLICATION PROCEDURE

It is recommended that the sealer be brushed, rolled or sprayed onto the completely clean and dry surface to be sealed. The surface **MUST BE COMPLETELY DRY**. Shield glass doors, windows and plants from spray to avoid damage. Allow the sealer to be absorbed into the surface in a saturation coat without puddles before applying a second and third coat. Apply 3 coats **WITHIN 2 HOURS** for maximum protection. Allow the surface to dry completely for 24 to 48 hours. We recommend that the surface be resealed every 2 to 3 years, or when water visibly darkens the surface.

PRODUCT FEATURES

- Repels water and oil based stains
- Water resistant finish
- Invisible barrier
- Non yellowing
- Provides abrasion resistance
- Excellent heat resistance
- Chemical inertness

CLEAN UP PROCEDURE

Clean equipment with mineral spirits including the sprayer head between applications.

TYPICAL PROPERTIES

Appearance:	Clear colorless liquid
Ionic Nature:	NA
Odor:	Hydrocarbon
Specific Gravity:	0.80 g/ml
pH:	NA
Compatibility:	Do not mix this product with any other chemicals

PACKAGING

This product is available in a one gallon plastic bottle or a 5 gallon plastic pail.

SAFETY

Harmful or fatal if swallowed. Keep out of reach of children and pets. Use gloves where necessary.

